


X vehicle with front engine
XX vehicle with rear engine

120 inch long flexible hydraulic hose

electrical connection:
1 ph, N+PE, 208/230V, 50/60Hz
17A delay fuse



(*) optional:
A concrete quality of min. C20/25
and a thickness of min. 6.5" is necessary
if the lift is mounted on a foundation.

Every solid and leveled surface
is suitable as location.

Sprinter mobil 7000
lifting capacity 7000 lbs

own weight: ca. 1060 lbs

Alle Maße in mm! / all dimensions in mm!
Mass- und Konstruktionsänderungen vorbehalten! dimensions and design changes reserved!

025SPB00110 (3D CAD-Modell)				Projektionsmethode 1 ISO 5456-2	
ind.	Aender. / modification	Datum	Name	Datum	Name
-	-	-	-	Bearb.	15.05.2019 MH
-	-	-	-	Gepr.	
-	-	-	-		
-	-	-	-		
-	-	-	-		
-	-	-	-		
-	-	-	-		
-	-	-	-		
-	-	-	-		

Nussbaum
Korker Str. 24, 77694 Kehl
www.nussbaum-group.de

Benennung / designation
Sprinter Mobil 7000

version for USA

Zeichnungsnummer / drawing number

8857_NB